

Airex Filter Corporation

# Superflow 24

High Velocity Low Airflow Resistance HEPA Filter

**AIREX FILTER**  
CORPORATION

**Longer Life – Gasket seal SuperFlow 24 filters have 400 sq. ft. of media compared to 240 sq. ft. for traditional HEPA filters. The greater media area provides a longer time period between filter replacements.**

**Improved Efficiency – The significant quantity of media translates into an extremely low media velocity. Therefore, a minimum overall efficiency of 99.99% at 0.30  $\mu$ m is easily assured. Traditional HEPA filters have an overall efficiency of 99.97% at 0.30  $\mu$ m.**

**Lower Operating Cost – The typical HEPA filter pressure drop can range from 1.4" w.g. to 1.8" w.g. at the rated airflow. The pressure drop of the SuperFlow 24 is 1" w.g. at the rated airflow.**

For more information, please visit our informational website  
[www.AirexFilter.com](http://www.AirexFilter.com)

**Register today for online ordering:**

Shop our full line of commercial filtration products:

**[www.Airexco.com](http://www.Airexco.com)**

- featuring unique volume discounts
- quick re-order from history
- various shipping and payment options

The Airex Filter SuperFlow 24 is a V-bed HEPA filter (99.99% at 0.30 micrometer) specifically designed for high airflow applications requiring HEPA efficiency at an ultra low-pressure drop. The SuperFlow 24 can be incorporated into systems with air velocities of 600 fpm and a pressure drop of 1" w.g.

## Product Design

The SuperFlow 24 filters are manufactured with wet laid microfine fiberglass media. The media is formed into a mini-pleat utilizing a hot melt separator and arranged in a V-bed configuration. There are twelve individual mini-pleat packs sealed on all four sides to the frame with two-component polyurethane. The frame is constructed of galvanized, aluminum, or stainless steel and consists of vertical support struts of the same material. Vertical supports are attached to the frame body without the use of mechanical fasteners. The vertical supports act as the sealing surface of the mini-pleat packs.

## Product Options

The SuperFlow 24 filters are available in aluminum, galvanized, or stainless steel frames and with gasket seal or gel seal design. The SuperFlow 24 filters are UL 900 Classified.

### Gasket Seal

The filter gasket is ¼" x ¾" black neoprene attached to the frame with an adhesive, and the gasket joints are dovetailed to ensure no penetration of particulate due to the gasket. The filter is designed for installation into front load holding frames, C-3 Gasket Seal Housing and Surelock-B Side Access Housing.

### Gel Seal

The filter gasket is BluJel® filled into a channel around the perimeter of the frame. The gel seal design provides the highest degree of sealing integrity between the filter and holding device.

Filter Depth	12"
Media Type	Fiberglass
Frame Material	Galvanized Steel    Stainless Steel    Aluminum
Max Operating Temperature	175°F (79°C)

